

04/09/98
3c494 U.S. PTO

Please type a plus sign (+) inside this box → ☒

PTO/SB/05 (12/97)
Approved for use through 09/30/00 OMB 0651-0032
Patent and Trademark Office U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. RCA 88,915 Total Pages 32

First Named Inventor or Application Identifier

Mehmet Kemal Ozkan

Express Mail Label No. EE121622754US

APPLICATION ELEMENTS
See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☒ Fee Transmittal Form
(Submit an original, and a duplicate for fee processing)
2. ☒ Specification [Total Pages 25]
(preferred arrangement set forth below)
 - Descriptive title of the invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the invention
 - Brief Summary of the invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 USC 113) [Total Sheets 7]
4. Oath or Declaration [Total Pages 1]
 - a. ☒ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 17 completed)
(Note Box 5 below)
 - i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation By Reference (useable if Box 4b is checked)
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

6. ☐ Microfiche Computer Program (Appendix)
7. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) ☒ Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☒ Information Disclosure Statement (IDS)/PTO-1449 ☒ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
14. ☐ Small Entity ☐ Statement filed in prior application, Statement(s) ☐ Status still proper and desired
15. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
16. ☐ Other:

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: _____

18. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label

or ☐ Correspondence address below

(Insert Customer No. or Attach bar code label here)

NAME	Joseph S. Tripoli				
	GE and RCA Licensing Management Operation, Inc.				
ADDRESS	Two Independence Way, PO Box 5312				
	Patent Operation				
CITY	Princeton	STATE	NJ	ZIP CODE	08543-5312
COUNTRY	USA	TELEPHONE	609/734-9503	FAX	609/734-9700

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

GE and RCA Licensing Management Operation, Inc.
Patent Operations
PO Box 5312
Princeton, NJ 08543-5312

Honorable Assistant Commissioner for Patents
Washington, D.C. 20231

Application for U.S. Letters Patent
RCA 88,915

Sir:

Date: April 9, 1998

Enclosed herewith, are the following:

(1) Application for Letters Patent:

Applicant(s) Mehmet Kemal Ozkan, Chia-Yuan Teng and
Edwin Arturo Heredia

For: A SYSTEM FOR FORMING AND PROCESSING PROGRAM MAP INFORMATION
SUITABLE FOR TERRESTRIAL, CABLE OR SATELLITE BROADCAST

Date(s) Executed April 2, 1998, April 5, 1998 and March 18, 1998 respectively.

Number of sheets of drawing Seven (7)


(2) Assignment for the above-identified application.

(3) The required fees are calculated as follows.

Basic Filing Fee	\$790
Additional Fees:	
Total number of claims, less 20 <u>4</u> x \$22.00 =	88
Number of independent claims, less 3 <u>3</u> x \$82.00 =	246
Total Filing Fee	1124.00
Fee for recording Assignment	\$ 40.00
Total	\$ 1164.00

Please charge the fee and any additional fee required or credit any overpayment to Deposit Account No. 07-0832.
A copy of this letter is enclosed for this purpose

Respectfully,



Alexander J. Burke

Attorney/~~AMH~~

Reg. No. 40,425

For telephone interview

call Alexander J. Burke

Telephone 609-734 - 9503

Transmit in Triplicate
Original for Patent
and Trademark Office

5 A system for Forming and Processing Program Map
Information Suitable for terrestrial, cable or satellite
Broadcast

10 This is a non-provisional application of provisional
application serial No. 60/052,152 by E. A. Heredia et al, filed July
10, 1997.

Field of the Invention

15 This invention is related to the formation of Program
Guides, system information and program specific information for
MPEG compatible processing.

Background of the Invention

20 In video broadcast and processing applications, digital
video data is typically encoded to conform to the requirements of
a known standard. One such widely adopted standard is the
MPEG2 (Moving Pictures Expert Group) image encoding standard,
25 hereinafter referred to as the "MPEG standard". The MPEG
standard is comprised of a system encoding section (ISO/IEC
13818-1, 10th June 1994) and a video encoding section (ISO/IEC
13818-2, 20th January 1995). Data encoded to the MPEG standard
is in the form of a packetized datastream which typically includes
30 the data content of many program channels (e.g. content
corresponding to cable television channels 1-125). Further,
several digital services and channels may occupy the frequency
spectrum previously occupied by a single analog channel. A 6 MHz
bandwidth previously allocated to an analog NTSC compatible
35 broadcast channel may now be split into a number of digital sub-
channels offering a variety of services. For example, the broadcast
spectrum for RF channel 13 may be allocated to sub-channels
including a main program channel, a financial service channel
offering stock quotes, a sports news service channel and a
40 shopping and interactive channel. In addition, both the quantity
of sub-channels transmitted and the individual sub-channel

5 bandwidth may be changed dynamically to accommodate changing broadcast programming requirements.

10 In such a digital video system the proliferation in the quantity of services being broadcast and the increased variety of their content, as well as the ability of a broadcaster to dynamically vary the number and allocated bandwidth of these channels poses a number of problems. Specifically, the increase in the quantity of broadcast channels may increase the difficulty of tuning and lengthen the time required to acquire a selected program channel. Further, as the quantity of channels increases so
15 does the quantity of ancillary program specific information required in decoding the transmitted program data. The ancillary program specific information includes data used in identifying and assembling packets comprising selected programs and also includes program guide and text information associated with the
20 transmitted program data. The increased quantity and variety of ancillary information transmitted places an additional burden on available transmission bandwidth and receiver decoding and storage resources.

25 In addition, channel numbering in such a digital video system may present a problem. This is because a broadcaster may not want to lose an original analog NTSC broadcast channel number even though the broadcaster is transmitting several program channels in the frequency spectrum previously occupied by the single analog program channel. The broadcaster may have
30 a significant investment in the channel number as a brand identity e.g. Fox 5TM, Channel 13TM. These problems and derivative problems are addressed by a system according to the present invention.

35 *Summary of the Invention*

40 In a digital video system for decoding an MPEG compatible datastream containing MPEG compatible program map table information, channel map information is identified and assembled. The channel map information identifies individual packetized datastreams that constitute a broadcast program. The

5 channel map information associates a broadcast channel with
packet identifiers used to identify individual packetized
datastreams that constitute a program transmitted in the
broadcast channel. The channel map information replicates
10 information conveyed in the MPEG compatible program map table
information.

Brief Description of the Drawings

In the drawing:

15 Figure 1 is a block diagram of digital video receiving
apparatus for demodulating and decoding broadcast signals,
according to the principles of the invention.

20 Figure 2 shows a Master Guide Table (MGT) format for
use in conveying program specific information, according to the
invention.

25 Figure 3 shows a Channel Information Table (CIT)
format for use in conveying program specific information
incorporating dual program channel identification numbers,
according to the invention.

30 Figure 4 shows a Service Location Descriptor (SLD)
format for use in conveying program specific information
incorporating program map information, according to the
invention.

35 Figure 5 shows a program specific information text
format for use in conveying program related text information,
according to the invention.

Figure 6 shows a scheme for assigning a text message
identifier as used in the text format of Figure 5.

5 Figure 7 shows a multiple compressed text string format for use in conveying program related text information, according to the invention.

10 Figures 8 and 9 show exemplary indicator definitions for compression and coding indicators within the multiple compressed text string format of Figure 7.

15 Figure 10 shows a method for generating program specific information according to the invention.

Detailed Description of the Drawings

20 Figure 1 is a block diagram of a digital video receiving system for demodulating and decoding broadcast signals, according to the principles of the invention. Although the disclosed system is described in the context of a system for receiving video signals incorporating program specific information including program guide data in MPEG compatible format, it is exemplary only. The program specific information may be of a variety of types. For example, it may comply with Program Specific Information (PSI) requirements specified in section 2.4.4 of the MPEG systems standard or it may comply with the high definition television (HDTV) signal standard *Digital Television Standard for HDTV Transmission* of April 12 1995, prepared by the United States Advanced Television Systems Committee (ATSC) or other ATSC standards. Alternatively, it may be formed in accordance with proprietary or custom requirements of a particular system.

35 The principles of the invention may be applied to terrestrial, cable, satellite, Internet or computer network broadcast systems in which the coding type or modulation format may be varied. Such systems may include, for example, non-MPEG compatible systems, involving other types of encoded datastreams and other methods of conveying program specific information. Further, although the disclosed system is described as processing broadcast programs, this is exemplary only. The term 'program' is

40

5 used to represent any form of packetized data such as audio data, telephone messages, computer programs, Internet data or other communications, for example.

10 In overview, in the video receiver system of Figure 1, a broadcast carrier modulated with signals carrying audio, video and associated data representing broadcast program content is received by antenna 10 and processed by unit 13. The resultant digital output signal is demodulated by demodulator 15. The demodulated output from unit 15 is trellis decoded, mapped into byte length data segments, deinterleaved and Reed-Solomon error corrected by decoder 17. The corrected output data from unit 17 is in the form of an MPEG compatible transport datastream containing program representative multiplexed audio, video and data components. The transport stream from unit 17 is demultiplexed into audio, video and data components by unit 22 which are further processed by the other elements of decoder system 100. In one mode, decoder 100 provides MPEG decoded data for display and audio reproduction on units 50 and 55 respectively. In another mode, the transport stream from unit 17 is processed by decoder 100 to provide an MPEG compatible datastream for storage on storage medium 105 via storage device 90.

30 A user selects for viewing either a TV channel or an on-screen menu, such as a program guide, by using a remote control unit 70. Processor 60 uses the selection information provided from remote control unit 70 via interface 65 to appropriately configure the elements of Figure 1 to receive a desired program channel for viewing. Processor 60 comprises processor 62 and controller 64. Unit 62 processes (i.e. parses, collates and assembles) program specific information including program guide and system information and controller 64 performs the remaining control functions required in operating decoder 100. Although the functions of unit 60 may be implemented as separate elements 62 and 64 as depicted in Figure 1, they may alternatively be implemented within a single processor. For example, the functions of units 62 and 64 may be incorporated within the programmed instructions of a

5 microprocessor. Processor 60 configures processor 13,
demodulator 15, decoder 17 and decoder system 100 to
demodulate and decode the input signal format and coding type.
Units 13, 15, 17 and sub-units within decoder 100 are
individually configured for the input signal type by processor 60
10 setting control register values within these elements using a bi-
directional data and control signal bus C.

The transport stream provided to decoder 100
comprises data packets containing program channel data and
program specific information. Unit 22 directs the program specific
15 information packets to processor 60 which parses, collates and
assembles this information into hierarchically arranged tables.
Individual data packets comprising the User selected program
channel are identified and assembled using the assembled
program specific information. The program specific information
20 contains conditional access, network information and identification
and linking data enabling the system of Figure 1 to tune to a
desired channel and assemble data packets to form complete
programs. The program specific information also contains ancillary
program guide information (e.g. an Electronic Program Guide -
25 EPG) and descriptive text related to the broadcast programs as
well as data supporting the identification and assembly of this
ancillary information.

The program specific information is assembled by
processor 60 into multiple hierarchically arranged and inter-
30 linked tables. An exemplary hierarchical table arrangement
includes a Master Guide Table (MGT), a Channel Information Table
(CIT), Event Information Tables (EITs) and optional tables such as
Extended Text Tables (ETTs). The MGT contains information for
acquiring program specific information conveyed in other tables
35 such as identifiers for identifying data packets associated with the
other tables. The CIT contains information for tuning and
navigation to receive a User selected program channel. The EIT
contains descriptive lists of programs (events) receivable on the
channels listed in the CIT. The ETT contains text messages
40 describing programs and program channels. Additional program
specific information describing and supplementing items within

5 the hierarchical tables is conveyed within descriptor information elements. The program specific information acquired by processor 60 via unit 22 is stored within internal memory of unit 60.

10 Considering Figure 1 in detail, a carrier modulated with signals carrying program representative audio, video and associated data received by antenna 10, is converted to digital form and processed by input processor 13. Processor 13 includes radio frequency (RF) tuner and intermediate frequency (IF) mixer and amplification stages for down-converting the input signal to a lower frequency band suitable for further processing. In this
15 exemplary system, the input signal received by antenna 10 contains 33 Physical Transmission Channels (PTCs 0-32). Each Physical Transmission Channel (PTC) is allocated a 6 MHz bandwidth and contains, for example, up to 6 sub-channels.

20 It is assumed for exemplary purposes that a video receiver user selects a sub-channel (SC) for viewing using remote control unit 70. Processor 60 uses the selection information provided from remote control unit 70 via interface 65 to appropriately configure the elements of decoder 100 to receive the PTC corresponding to the selected sub-channel SC. Following
25 down conversion, the output signal from unit 13 for the selected PTC has a bandwidth of 6 MHz and a center frequency in the range of 119-405 MHz. In the following discussion, an RF channel or Physical Transmission Channel (PTC) refers to an allocated broadcaster transmission channel band which encompasses one or
30 more sub-channels (also termed virtual or logical channels).

Processor 60 configures the radio frequency (RF) tuner and intermediate frequency (IF) mixer and amplification stages of unit 13 to receive the selected PTC. The down-converted frequency output for the selected PTC is demodulated by unit 15.
35 The primary functions of demodulator 15 are recovery and tracking of the carrier frequency, recovery of the transmitted data clock frequency, and recovery of the video data itself. Unit 15 also recovers sampling and synchronization clocks that correspond to transmitter clocks and are used for timing the operation of
40 processor 13, demodulator 15 and decoder 17. The recovered output from unit 15 is provided to decoder 17.

5 The output from demodulator 15 is mapped into byte
length data segments, deinterleaved and Reed-Solomon error
corrected according to known principles by unit 17. In addition,
unit 17 provides a Forward Error Correction (FEC) validity or lock
10 indication to processor 60. Reed-Solomon error correction is a
known type of Forward Error Correction. The FEC lock indication
signals that the Reed-Solomon error correction is synchronized to
the data being corrected and is providing a valid output. It is to be
noted that the demodulator and decoder functions implemented
by units 13, 15 and 17 are individually known and generally
15 described, for example, in the reference text *Digital
Communication*, Lee and Messerschmidt (Kluwer Academic Press,
Boston, MA, USA, 1988).

 The corrected output data from unit 17 is processed
by MPEG compatible transport processor and demultiplexer 22.
20 The individual packets that comprise either particular program
channel content, or program specific information, are identified by
their Packet Identifiers (PIDs). Processor 22 separates data
according to type based on an analysis of Packet Identifiers (PIDs)
contained within packet header information and provides
25 synchronization and error indication information used in
subsequent video, audio and data decompression.

 The corrected output data provided to processor 22 is
in the form of a transport datastream containing program channel
content and program specific information for many programs
30 distributed through several sub-channels. The program specific
information in this exemplary description describes sub-channels
present in a transport stream of a particular PTC. However, in
another embodiment the program specific information may also
describe sub-channels located in other PTCs and conveyed in
35 different transport streams. Groups of these sub-channels may be
associated in that their source is a particular broadcaster or they
occupy the transmission bandwidth previously allocated to an
analog NTSC compatible broadcast channel. Further, individual
packets that comprise a selected program channel in the transport
40 stream are identified and assembled by processor 60 operating in

5 conjunction with processor 22 using PIDs contained in the program specific information.

10 The program specific information is in the form of hierarchically arranged tables including an MGT, CIT, EIT, and ETT together with supplementary descriptor information. The PID that identifies packets comprising the MGT data is predetermined and stored within processor 60 internal memory. Further, the MGT conveys the PIDs that identify the CIT, EIT, and ETT data and conveys other information indicating the size of these tables. Processor 60 monitors the MGT for updates to identify any
15 changes in PIDs or table sizes. Therefore, after processor 60 determines from the FEC lock indication provided by unit 17 that valid data is being provided to transport processor 22, the MGT may be acquired without additional PID information. Using Control signal C, processor 60 configures transport processor 22 to select
20 the data packets comprising the remaining program specific information including the CIT, EIT and ETT data. Processor 22 matches the PIDs of incoming packets provided by unit 17 with PID values pre-loaded in control registers within unit 22 by processor 60. Further, processor 60 accesses, parses and
25 assembles the program specific information packets captured by processor 22 and stores the program specific information within its internal memory. Processor 60 derives tuning parameters including PTC carrier frequency, demodulation characteristics, and sub-channel PIDs, from the acquired program specific information. Processor 60 uses this information in configuring units 13, 15, 17
30 and decoder 100 elements to acquire selected sub-channel (SC) program content.

35 The program specific information including MGT, CIT, EIT, and ETT data and associated descriptors acquired and collated by processor 60 incorporates advantageous features exemplified in the data formats presented in Figures 2-9. These features facilitate the identification, acquisition, assembly and decoding of program channel content and associated program guide data by decoder 100 (Figure 1). Processor 60 forms a MGT as exemplified
40 by the data format of Figure 2 by accessing and assembling the program specific information packets that are stored in the unit

5 60 internal memory. The MGT contains data identifiers e.g. PID_ETT 205 and PID_PG 210 (Figure 2) enabling the assembly of the CIT, EIT and ETT tables. Processor 60 uses the MGT data identifiers to access and assemble the program specific information packets to form the CIT, EIT, and ETT data and
10 associated descriptors.

Processor 60 uses the acquired CIT channel map information, as exemplified in Figure 3, to identify the packets comprising the sub-channel SC that the User selected to view. A user selects sub-channel SC for viewing by entering two program
15 channel numbers via remote control unit 70 and interface 65. Individual program channels are advantageously allocated both a first and a second identification number. The first identification number (a major number as indicated by bundle_number 300 in Figure 3) identifies the broadcast source and broadcaster channel
20 brand number e.g. Fox 5™, Channel 13™. The first identification number indicates a broadcast source of a program or service and may be independent of the RF channel on which the program is broadcast. However, in other embodiments the first identification number may be associated with a broadcast RF channel or be
25 associated with other program characteristics such as a program category or theme e.g. movies. The second identification number (a minor number as indicated by channel_number_in_bundle 305 in Figure 3) identifies a sub-channel corresponding to a specific service within a group of services provided by a broadcaster. The
30 first and second identification numbers in conjunction identify a particular service as a sub-channel provided by a specific broadcaster. Although, the selected sub-channel SC may occupy an RF bandwidth within an encompassing channel spectrum associated with the broadcast source, neither the first or second
35 identification numbers are associated with such a spectrum. However, this association may be made in an alternative embodiment. This dual numbering system enables a broadcaster to retain channel brand identity across a range of dynamically allocable broadcast sub-channels.

40 The dual program channel identification numbers used to select sub-channel SC may be entered by the user in a variety

5 of ways. These may include using remote unit 70 to select sub-channel SC from within a hierarchical menu system displaying program channel selections in a program guide or by simple sequential number entry via the unit 70 keypad, for example. The channel selection system may also encompass the use of a
10 different data entry device such as a keyboard or discrete switches, for example. Further, the data entry system also accommodates the entry of a single channel identification number as well as dual identification numbers. Upon detecting a channel selection completion command, processor 60 converts a single
15 channel identification number entry into dual identification numbers. Processor 60 converts the single channel identification number to dual channel identification numbers in accordance with a predetermined conversion map. This conversion may also be performed using a predetermined and stored algorithm or
20 formula. The derived dual identification numbers are used by processor 60 for packet identification, tuning and for identifying other decoder information in the manner previously described as if both numbers had been entered by a user.

Processor 60 uses the received program channel
25 identification numbers 300 and 305 provided from remote control unit 70 via interface 65 to determine the PTC corresponding to the selected sub-channel SC from the CIT. Once the PTC number (item 315 in Figure 3) is determined, processor 60 (Figure 1) configures units 13, 15, and 17 to receive the PTC for the selected sub-
30 channel SC. The unique program sub-channel determined from the program channel identification numbers 300 and 305 may alternatively be termed a service or a virtual channel or a logical channel and the CIT may be deemed a virtual channel table. Further, as well as associating a particular PTC with first and
35 second sub-channel identification numbers 300 and 305 of selected sub-channel SC, the CIT also associates other parameters with SC. These parameters include (a) a channel_id 320 for linking the selected sub-channel SC with program content information conveyed in the EITs, (b) a channel_type indicator 325 identifying
40 whether the sub-channel data is, analog e.g. NTSC, digital video e.g. ATSC video or digital audio e.g. ATSC audio, (c) an ETM_flag

5 330 indicating whether a text message is available for this sub-channel, (d) a channel name 340 and (e) a descriptor 335 e.g. a Service Location Descriptor as described later.

Processor 60 advantageously determines program map information for the selected sub-channel SC from Service Location
10 Descriptor (SLD) conveyed within the CIT. The SLD program map information is exemplified by the data format of Figure 4. The SLD associates the selected sub-channel SC with packet identifiers, e.g. item 420, used to identify individual packetized datastreams that constitute the components of a program being transmitted on
15 selected sub-channel SC. In addition, the SLD program map information, in conjunction with the CIT, maps the selected sub-channel SC to a program number 405, a PCR (Program Clock Reference) identifier 410, a language code indicator 425, and a stream type identifier 415 identifying a stream as video, audio, control, auxiliary or private information, for example.
20

The SLD program map information replicates information already present within the Program Map Table (PMT) segment of the MPEG compatible transport stream input to decoder 100. However, by incorporating the SLD within the CIT,
25 the time required by decoder 100 to identify and acquire a program being transmitted on selected sub-channel SC is advantageously reduced. This is because the CIT and SLD provide formatted and linked information sufficient to enable processor 60 to directly configure and tune the system of Figure 1 to receive the selected sub-channel SC. Specifically, the CIT and SLD directly
30 associate individual first and second sub-channel identification numbers with the PIDs for identifying the datastreams that constitute a program being conveyed on this sub-channel. This enables processor 60 to configure the system of Figure 1 to receive the selected sub-channel SC without acquiring and using the Program Map Table (PMT) information in the MPEG compatible transport stream input to decoder 100. In addition, the data partitioning, data formatting and data repetition frequency characteristics of the CIT and SLD program map information may
35 be determined independently of the requirements of MPEG PMT information.
40

5 The packetized decoded transport stream input to
decoder 100 from unit 17 contains video, audio and data
representing TV programs, for example, and also contains sub-
picture data. The sub-picture data contains picture elements
10 associated with programs and channels selectable by a user for
viewing including program guides, display commands, subtitling,
selectable menu options or other items, for example. As such, the
sub-picture data includes the EIT containing descriptive lists of
programs (events) receivable on the sub-channels listed in the CIT
and also contains the ETT containing text messages describing
15 programs and program sub-channels.

Processor 60 determines from the CIT and SLD the
PIDs of the video, audio and sub-picture streams constituting the
program being transmitted on selected sub-channel SC. Processor
22, matches the PIDs of incoming packets provided by decoder 17
20 with PID values of the video, audio and sub-picture streams being
transmitted on sub-channel SC. These PID values are pre-loaded
in control registers within unit 22 by processor 60. In this
manner, processor 22 captures packets constituting the program
transmitted on sub-channel SC and forms them into MPEG
25 compatible video, audio and sub-picture streams for output to
video decoder 25, audio decoder 35 and sub-picture processor 30
respectively. The video and audio streams contain compressed
video and audio data representing the selected sub-channel SC
program content. The sub-picture data contains the EIT and ETT
30 information associated with the sub-channel SC program content.

Decoder 25 decodes and decompresses the MPEG
compatible packetized video data from unit 22 and provides
decompressed program representative pixel data to NTSC encoder
45 via multiplexer 40. Similarly, audio processor 35 decodes the
35 packetized audio data from unit 22 and provides decoded and
amplified audio data, synchronized with the associated
decompressed video data, to device 55 for audio reproduction.
Processor 30 decodes and decompresses sub-picture data received
from unit 22.

40 The sub-picture data decoded by processor 30
includes text messages (Extended Text Messages - ETMs) in an ETT

5 in the exemplary data format presented in Figure 5. The text
messages conveyed in the ETT of Figure 5 are advantageously
partitioned into time periods of specified duration. The segmented
text messages describe programs occurring in a period of specified
10 duration and start time e.g. 3 hour blocks starting from 12 a.m., 3
p.m., 6 p.m.... etc. Indicators defining the duration and start time
applicable to the conveyed text messages are included in the MGT
of Figure 2 (duration item 215 and application_time item 220 of
Figure 2 respectively). A text message (e.g.
15 extended_text_message 505) is conveyed together with a text
message identifier (ETM_id 510) in the format of Figure 5.

20 Decoder 100 (Figure 1) is able to more efficiently
acquire, process and store program descriptive text messages that
are partitioned into time periods of specified duration than is
possible in the absence of such segmentation. This is because
segmented text messages exclude information occurring outside
the specified time period and consequently are smaller than non-
segmented text messages. Therefore, segmented text message data
occupies less storage space and can be acquired and processed
25 more quickly than larger data blocks of non-segmented data.
Further, the data format of Figure 5 allows a user to acquire text
message data for a selected sub-channel SC or a group of selected
program sub-channels. This allows the identification, acquisition
and decoding of text message data by decoder 100 to be focused
30 on the programs and sub-channels of interest to a user and
reduces the acquisition of redundant text message information.

A text message conveyed in an ETT may contain
channel information or program (event) information. Figure 6
shows an exemplary format for assigning a text message identifier
ETM_id 510 of Figure 5 that identifies the type of text message
35 e.g. whether the text message contains channel information (item
610 of Figure 6) or program information (item 605 of Figure 6).
The text message identifier 510 (Figure 5) also identifies the
source e.g. sub-channel to which the text message pertains.

40 A text message 505 conveyed in the ETT of Figure 5 is
compressed and formatted according to the multiple compressed
text string format of Figure 7. The compressed text string format

5 advantageously incorporates indicators facilitating the
identification and decoding of multiple compressed text strings by
processor 30 in decoder 100 of Figure 1. Processor 30 decodes text
string 505 (Figure 5) received from unit 22 (Figure 1) by
10 determining the compression, coding and language characteristics
of the text string from indicators 705, 710 and 715 (Figure 7)
respectively. Specifically, processor 30, operating in conjunction
with processor 60, decompresses received text string 505 by
applying a decompression function e.g. a Huffman decompression
15 function, selected using indicator 705. Similarly, processor 30,
decodes the received text string by applying a decoding function
interpreting text characters according to a character code set
selected using indicator 710 and a language code set selected
using indicator 715. Further, processor 30 determines the number
20 of text strings to be processed and the number of bytes in each
text string from indicators 725 and 720 respectively.

Figure 8 shows an exemplary indicator definition for
compression indicator 705 within the multiple compressed text
string format of Figure 7. It is to be noted that compression
indicator 705 may indicate that no compression function is
25 employed within a text string. In this case, processor 30 does not
apply a decompression function to the text string received from
unit 22. Figure 9 shows an exemplary indicator definition for
coding indicator 710 within the multiple compressed text string
format of Figure 7.

30 Processor 30 assembles and formats the decoded and
decompressed text string elements of text string 505 (Figure 5) to
form a decoded text string for output to On-Screen Display (OSD)
and graphics generator 37 (Figure 1). Unit 37 interprets and
formats the text string character data from unit 30 and generates
35 formatted pixel mapped text and graphics for presentation on unit
50. The formatted pixel mapped text and graphics data may
represent a program guide or other type of menu or user interface
for subsequent display on unit 50. Unit 37 also processes EIT, ETT
and other information to generate pixel mapped data
40 representing, subtitling, control and information menu displays
including selectable menu options, and other items, for

5 presentation on unit 50. The control and information displays enable function selection and entry of device operating parameters for User operation of decoder 100.

10 The text and graphics produced by OSD generator 37 are generated in the form of overlay pixel map data under direction of processor 60. The overlay pixel map data from unit 37 is combined and synchronized with the decompressed pixel representative data from MPEG decoder 25 in encoder 45 via multiplexer 40 under direction of processor 60. Combined pixel map data representing a video program on sub-channel SC
15 together with associated sub-picture text message data is encoded by NTSC encoder 45 and output to device 50 for display.

20 In a storage mode of the system of Figure 1, the corrected output data from unit 17 is processed by decoder 100 to provide an MPEG compatible datastream for storage. In this mode, a program is selected for storage by a user via remote unit 70 and interface 65. Processor 22, in conjunction with processor 60 forms condensed program specific information including MGT, CIT, EIT and ETT data and descriptors containing the advantageous features previously described. The condensed program specific
25 information supports decoding of the program selected for storage but excludes unrelated information. Processor 60, in conjunction with processor 22 forms a composite MPEG compatible datastream containing packetized content data of the selected program and associated condensed program specific information. The composite
30 datastream is output to storage interface 95.

Storage interface 95 buffers the composite datastream to reduce gaps and bit rate variation in the data. The resultant buffered data is processed by storage device 90 to be suitable for storage on medium 105. Storage device 90 encodes the buffered
35 datastream from interface 95 using known error encoding techniques such as channel coding, interleaving and Reed Solomon encoding to produce an encoded datastream suitable for storage. Unit 90 stores the resultant encoded datastream incorporating the condensed program specific information on medium 105.

40 Figure 10 shows a method for generating program specific information including MGT, CIT, EIT and ETT data and

5 descriptors containing the advantageous features previously described. The method may be employed at an encoder for broadcasting video data such as the data received by antenna 10 of Figure 1 or the method may be employed within a decoder unit such as within processor 60 of Figure 1.

10 Following the start at step 800 of Figure 10, a CIT is generated in step 810. The CIT contains sub-channel and program identification information enabling acquisition of available broadcast programs and sub-channels. The CIT incorporates first and second sub-channel identification numbers and an SLD
15 containing packet identifiers for identifying individual packetized datastreams that constitute individual programs to be transmitted on particular sub-channels. The generated CIT also incorporates items linked to listed program sub-channels including a program number, a PCR (Program Clock Reference) identifier, a language
20 code indicator, and a stream type identifier, as previously described in connection with Figure 1.

In step 815, an EIT is generated containing program guide information including descriptive lists of programs (events) receivable on the sub-channels listed in the CIT. In step 820, an
25 ETT is generated containing text messages describing programs, for example. Each text message is partitioned into time periods of specified duration. The duration and application time of the segmented text message data is also defined by indicators in the ETT itself. The text message data is encoded and compressed
30 according to known techniques and conveyed in the ETT along with indicators defining the compression, coding and language characteristics employed. The ETT is also generated to include indicators defining the number of text strings to be processed and the number of bytes in each text string. In step 822 an MGT is
35 generated containing data identifiers enabling the identification and assembly of CIT, EIT and ETT information. The MGT also conveys table size information for the previously generated CIT, EIT and ETT.

40 In step 825, program specific information is formed including the MGT, CIT, EIT and ETT data and descriptors generated in steps 805-822. In step 830, the program specific

5 information together with video and audio program
representative components for multiple sub-channels is formatted
into a transport stream for output. In step 835, the output
transport stream is further processed to be suitable for
transmission to another device such as a receiver, video server, or
10 storage device for recording on a storage medium, for example.
The processes performed in step 835 include known encoding
functions such as data compression Reed-Solomon encoding,
interleaving, scrambling, trellis encoding, and carrier modulation.
The process is complete and terminates at step 840. In the process
15 of Figure 10, multiple CIT, EIT and ETT tables may be formed and
incorporated in the program specific information in order to
accommodate expanded numbers of sub-channels.

The architecture of Figure 1 is not exclusive. Other
architectures may be derived in accordance with the principles of
the invention to accomplish the same objectives. Further, the
20 functions of the elements of decoder 100 of Figure 1 and the
process steps of Figure 10 may be implemented in whole or in
part within the programmed instructions of a microprocessor. In
addition, the principles of the invention apply to any form of
25 MPEG or non-MPEG compatible electronic program guide. A
datastream formed according to the invention principles may be
used in a variety of applications including video server or PC type
communication via telephone lines, for example. A program
datastream with one or more components of video, audio and data
30 formed to incorporate program specific information according to
invention principles may be recorded on a storage medium and
transmitted or re-broadcast to other servers, PCs or receivers.
Further, any reference herein to "bandwidth" is to be interpreted
expansively to include bit rate capacity and is not limited to a
35 frequency spectrum, for example.

5 What is claimed is:

10 1. Apparatus for decoding a datastream of MPEG compatible packetized program information containing program map table information to provide decoded program data, comprising:

15 means for identifying channel map information conveyed within said packetized program information, said channel map information associating a broadcast channel with packet identifiers used to identify individual packetized datastreams that constitute a program transmitted in said broadcast channel; and

20 means for assembling said identified information to form a channel map for identifying said individual packetized datastreams constituting said program, wherein

25 said channel map information replicates information conveyed in said MPEG compatible program map table information.

30 2. Apparatus according to claim 1, wherein said channel map information further associates an individual program with a corresponding program clock reference (PCR) value.

35 3. Apparatus according to claim 1, wherein said channel map information further associates an individual program with a corresponding language type indicator.

40 4. Apparatus according to claim 1, wherein said channel map information further associates an individual program with a corresponding physical transmission channel carrier frequency.

5. Apparatus according to claim 1, including means for tuning to receive said program transmitted on said broadcast channel using said channel map information for acquisition of said program.

5

6. Apparatus according to claim 1, wherein
said channel map information further associates said
packet identifiers with first and second identification numbers
used in conjunction to identify said broadcast channel.

10

7. Apparatus according to claim 6, wherein
said decoder acquires said program transmitted on
said broadcast channel in response to User entry of said first and
second identification numbers.

15

8. Apparatus according to claim 1, wherein
said information associating said broadcast channel
with said packet identifiers is conveyed within a descriptor
section of said channel map information.

20

9. Apparatus according to claim 8, wherein
said channel map information associates a plurality of
broadcast channels with corresponding descriptor sections.

25

10. Apparatus according to claim 1, wherein
said channel map information further associates a
datastream type indicator with an individual packetized
datastream, said datastream type indicator identifying whether
said individual packetized datastream contains at least one of a)
audio information, and b) video information.

30

5 11. Apparatus for decoding MPEG compatible packetized program information to provide decoded program data, comprising:

 means for identifying channel map information conveyed within said packetized program information, said
10 channel map information associating a broadcast channel with packet identifiers used to identify individual packetized datastreams that constitute a program transmitted in said broadcast channel; and

 means for assembling said identified information to
15 form a channel map for identifying said individual packetized datastreams constituting said program, wherein

 said channel map information associates an individual program with a corresponding language type indicator.

20 12. Apparatus according to claim 11, wherein
 said channel map information associates an individual program with a corresponding program clock reference (PCR) value.

25 13. A storage medium containing MPEG compatible digital data representing video information comprising:

 a video program;

 MPEG compatible program map table information; and

 channel map information contained within said MPEG
30 compatible digital data, said channel map information associating packet identifiers with individual packetized datastreams that constitute said video program, wherein

 said channel map information replicates information conveyed in said MPEG compatible program map
35 table information.

 14. A storage medium according to claim 13, wherein
 said channel map information further associates an individual program with a corresponding language type indicator.

5 15. A storage medium according to claim 13, wherein
said channel map information further associates an
individual program with a corresponding program clock reference
(PCR) value.

10 16. Apparatus for forming program guide information
suitable for decoding MPEG compatible packetized program
information containing program map table information to provide
decoded program data, comprising:

15 means for forming channel map information including
information associating a broadcast channel with packet
identifiers used to identify individual packetized datastreams that
constitute a program transmitted in said broadcast channel; and

 means for incorporating said channel map information
into packetized program guide information for output, wherein

20 said channel map information replicates
information conveyed in said MPEG compatible program map
table information.

25 17. Apparatus according to claim 16, wherein
said channel map information further associates an
individual program with a corresponding program clock reference
(PCR) value.

30 18. Apparatus according to claim 16, wherein
said channel map information further associates an
individual program with a corresponding language type indicator.

35 19. Apparatus according to claim 16, wherein
said channel map information further associates said
packet identifiers with first and second identification numbers
used in conjunction to identify said broadcast channel.

40 20. Apparatus according to claim 16, wherein
said information associating said broadcast channel
with said packet identifiers is conveyed within a descriptor
section of said channel map information.

5

21. Apparatus according to claim 20, wherein
said channel map information associates a plurality of
broadcast channels with corresponding descriptor sections.

10

22. Apparatus according to claim 16, wherein
said channel map information further associates a
datastream type indicator with an individual packetized
datastream, said datastream type indicator identifying whether
said individual packetized datastream contains at least one of a)
15 audio information, and b) video information.

20

23. A method for decoding MPEG compatible
packetized program information containing program map table
information to provide decoded program data, comprising the
steps of:

25

identifying channel map information conveyed within
said packetized program information, said channel map
information associating a broadcast channel with packet
identifiers used to identify individual packetized datastreams that
constitute a program transmitted on said broadcast channel; and

30


assembling said identified information to form a
channel map suitable for use in identifying said individual
packetized datastreams constituting said program, wherein
said channel map information replicates
information conveyed in said MPEG compatible program map
table information.

- 5 24. A method for forming program guide information
suitable for decoding MPEG compatible packetized program
information containing program map table information to provide
decoded program data, comprising the steps of:
- 10 forming channel map information including
information associating a broadcast channel with packet
identifiers used to identify individual packetized datastreams that
constitute a program transmitted on said broadcast channel; and
 incorporating said channel map information into
packetized program guide information for output, wherein
- 15 said channel map information replicates
information conveyed in said MPEG compatible program map
table information.

2011-03-04 10:00:00

1. *Pharmaceutical Innovation and the Role of the State*
 2. *The Impact of Patent Law on Drug Development*
 3. *The Role of Government in Regulating Pharmaceuticals*
 4. *The Impact of Health Insurance on Drug Access*
 5. *The Role of the Pharmaceutical Industry in Public Health*
 6. *The Impact of Globalization on Drug Markets*
 7. *The Role of the Pharmaceutical Industry in Developing Countries*
 8. *The Impact of Intellectual Property on Drug Innovation*
 9. *The Role of the Pharmaceutical Industry in Health Care Reform*
 10. *The Impact of the Pharmaceutical Industry on the Environment*

1. *Pharmaceutical Innovation and the Role of the State*
 2. *The Impact of Patent Law on Drug Development*
 3. *The Role of Government in Regulating Pharmaceuticals*
 4. *The Impact of Health Insurance on Drug Access*
 5. *The Role of the Pharmaceutical Industry in Public Health*
 6. *The Impact of Globalization on Drug Markets*
 7. *The Role of the Pharmaceutical Industry in Developing Countries*
 8. *The Impact of Intellectual Property on Drug Innovation*
 9. *The Role of the Pharmaceutical Industry in Health Care Reform*
 10. *The Impact of the Pharmaceutical Industry on the Environment*



Bit Stream Syntax for the Master Guide Table

Syntax	Bits	Format
master_guide_table_section () {		
table_id	8	0xE0
section_syntax_indicator	1	'1'
private_indicator	1	'1'
reserved	2	'11'
private_section_length	12	uimsbf
table_id_extension	16	0x0000
reserved	2	'11'
version_number	5	uimsbf
current_next_indicator	1	'1'
section_number	8	0x00
last_section_number	8	0x00
reserved	3	'111'
CRT_version_number	5	uimsbf
zero	4	'0000'
num_pg	4	uimsbf
for (i=0;i< num_pg;i++) PG(i) {		
application_time	40	uimsbf
duration	16	uimsbf
reserved	2	'11'
CIT_flag	1	blsbf
num_bytes	21	uimsbf
reserved	3	'111'
PID_PG [i]	13	uimsbf
reserved	3	'111'
PID_ETT [i]	13	uimsbf
reserved	4	uimsbf
PG_descriptors_length	12	uimsbf
for(j = 0;i< M;j++)		
descriptor ()	var	
}		
reserved	4	uimsbf
descriptors_length	12	uimsbf
for (i = 0;i< N;j++)		
descriptor ()	var	
CRC_32	32	rpchof
}		

FIGURE 2

Bit Stream Syntax for the Channel Information Table

Syntax	Bits	Format
channel_guide_table_section () {		
table_id	8	0xE3
section_syntax_indicator	1	'1'
private_indicator	1	'1'
reserved	2	'11'
section_length	12	uimbsf
table_id_extension	16	uimbsf
reserved	2	'11'
version_number	5	uimbsf
current_next_indicator	1	'1'
section_number	8	uimbsf
last_section_number	8	uimbsf
num_channels_in_section	8	uimbsf
for (k=0; k<num_channels_in_section; k++) cha_info(k){		
short_name	8*6	ISO-639
channel_visibility	32	bslbf
bundle_channel_number {		
bundle_number	12	uimbsf
channel_number_in_bundle	12	uimbsf
}		
Channel_PTC	8	uimbsf
channel_id	16	uimbsf
channel_type	8	uimbsf
reserved	3	'111'
ETM_flag	1	bslbf
descriptors_length	12	uimbsf
for (i=0; i<N; i++){		
descriptors()		
}		
}		
CRC_32	32	rpchbf
}		

FIGURE 3

Bit Stream Syntax for the Service Location Descriptor

Syntax	Bits	Format
service_location_descriptor () {		
405 descriptor_tag	8	uimsbf
descriptor_length	8	uimsbf
program_number	16	uimsbf
410 reserved	3	'111'
PCR_PID	13	uimsbf
number_PIDs	8	uimsbf
415 for (i=1;i<number_PIDs;i++){		
stream_type	8	uimsbf
420 reserved	3	bslbf
elementary_PID	13	uimsbf
ISO_639_language_code	8*3	uimsbf
425 }		
}		
}		

FIGURE 4

Bit Stream Syntax for the Service Location Descriptor

Syntax	Bits	Format
extended_text_table_section () {		
table_id	8	0xE5
section_syntax_indicator	1	'0'
private_indicator	1	'1'
reserved	2	'11'
510 private_section_length	12	uimsbf
ETM_id	32	bslbf
505 extended_text_message ()	var	
}		

FIGURE 5

Bit	1	2	3	18	19	32
610 channel ETM_id	0	0	channel_id	111.....11		
605 event ETM_id	1	0	channel_id	event_id		

FIGURE 6

Bit Stream Syntax for the Service Location Descriptor

Syntax	Bits	Format
multiple_compressed_strings () {		
number_strings	8	uimsbf
for (i = 0; i < number_strings; i++) {		
number_bytes	16	uimsbf
ISO_639_language_code	8*3	uimsbf
coding_indicator	8	bslbf
compression_type	8	uimsbf
for (j = 0; j < number_bytes; j++)		
compressed_string_byte [j]	8	uimsbf
}		
}		

FIGURE 7


compression_type	compression method
0x00	No compression
0x01	Huffman coding based on the default Huffman table
0x02	LZW
0x03 to 0xAF	reserved
0xB0 to 0xFF	user private

FIGURE 8

coding_indicator	coding method
0x00	Unicode
0x01	Latin-1
0x02	Latin-2
0x03 to 0xAF	reserved
0xB0 to 0xFF	user private

FIGURE 9

FIGURE 10



DECLARATION AND POWERS OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled **A SYSTEM FOR FORMING AND PROCESSING PROGRAM MAP INFORMATION SUITABLE FOR TERRESTRIAL, CABLE OR SATELLITE BROADCAST**

the specification of which was filed on _____ as Application Serial No. _____ and was amended on _____, or, if not identified here by filing date and serial number, is attached hereto.

I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 USC 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate by me or my representatives or assigns for this invention having a filing date before that of the application on which priority is claimed.

Application No. _____ in _____ on _____ priority claimed ☐ Yes ☐ No

Application No. _____ in _____ on _____ priority claimed ☐ Yes ☐ No

Application No. _____ in _____ on _____ priority claimed ☐ Yes ☐ No

I hereby claim the benefit under 35 USC 119(e) of any United States provisional application(s) as listed below.

Application No. 60/052,152 Filed 07/10/97

Application No. _____ Filed _____

I hereby claim the benefit under 35 USC 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of 35 USC 112, I acknowledge the duty to disclose material information as defined in 37 CFR 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application

Serial No. _____ Filed _____ ☐ patented ☐ pending ☐ abandoned

Serial No. _____ Filed _____ ☐ patented ☐ pending ☐ abandoned

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 USC 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

I hereby appoint, individually and collectively, the following as my/our attorney or agent with full power of substitution and revocation, to prosecute this application and to transact all business in the U.S. Patent and Trademark Office connected therewith:

Joseph S. Tripoli _____ Registration No. 26,040 and
 Ronald H. Kurdyla _____ Registration No. 26,932 and
 Alexander J. Burke _____ Registration No. 40,425 and
 _____ Registration No. _____

PLEASE ADDRESS ALL

COMMUNICATIONS TO: JOSEPH S. TRIPOLI

PATENT OPERATIONS - GE AND RCA
 LICENSING MANAGEMENT OPERATION, INC.
 CN 5312
 PRINCETON, NEW JERSEY 08543-0028

Sole or Joint Inventor (1)	Mehmet Kemal Ozkan	<i>Mehmet Kemal Ozkan</i>
	(Type or Print)	(Signature in Full. No initials.)
Citizenship	Turkey	Date 4/2/98
Post Office Address	4043 Braided Stream Way, #3A, Indianapolis, Indiana 46268	
Residence	Indianapolis, Marion County, Indiana 46268	
Sole or Joint Inventor (2)	Chia-Yuan Teng	<i>Chia-Yuan Teng</i>
	(Type or Print)	(Signature in Full. No initials.)
Citizenship	Taiwan	Date 4/5/98
Post Office Address	11825 Caminito Ronaldo, Apt. #119, San Diego, California 92128	
Residence	San Diego, San Diego County, California 92128	
Sole or Joint Inventor (3)	Edwin Arturo Heredia	<i>Edwin Arturo Heredia</i>
	(Type or Print)	(Signature in Full. No initials.)
Citizenship	Bolivia	Date March 18, 1998
Post Office Address	8356 Lakeshore Trace East Drive, Indianapolis, Indiana 46250	
Residence	Indianapolis, Marion County, Indiana 46250	